

R15L100-SPC369-U

15" IP69K Stainless U Series Display



KEY FEATURES

- Full IP69K waterproof and dustproof
- SUS 316 / AISI 316 Flat Stainless
- I.T.E. for Class I, Division 2, Groups A, B, C, D; T-Code T4 for hazardous area applications
- Touch Screen, Tempered Glass
- VESA mount, Yoke mount
- Rotary switch touch mode for Hand/Rain/Glove application



SPECIFICATIONS

Display	
Resolution	1024x768
Contrast Ratio	2000:1
Display Color	16.2M Colors
Active Area	304.1x228.1 mm
Size	15 inches
Panel Brightness	300 nits
View Angles	88,88,88,88
Touch / Glass	Projected Capacitive Multi Touch Screen
Mechanical	
Dimension	378 x 305 x 74 mm
Enclosure	Stainless Housing
Mounting	VESA Mount Yoke Mount
Cooling System	Fanless design
Environment	
Operating Humidity	10% to 90% (non-condensing)
Storage Temperature	-20~60°C
Operating Temperature	0~45°C
IP rating	IP69K
Certification	
Certification	CE, FCC UL 50E NEMA/UL Type 2 or NEMA/UL Type 12/4/4X, IP69K Hazardous Location: I.T.E. for Class I, Division 2, Groups A, B, C, D; T-Code T4 UL62368-1
IO Ports	
USB Port	1 x M12 waterproof connector for touch screen control
Video	1x M12 type connector for VGA input 1x waterproof connector for DVI input (Optional) 1x waterproof connector for HDMI input (Optional)
Indicator	1 x LED Indicator for power 1 x LED Indicator for status
Accessory	
Accessory	100~240V AC to DC Adapter with waterproof connector Power Cord External USB cable with waterproof connector for touchscreen control External VGA cable with waterproof connector Waterproof caps Manual VESA screws
Optional Accessory	External HDMI cable with waterproof connector (Optional) External DVI cable with waterproof connector (Optional)

Control

Button	1 x Power Button 1 x Adjust up button 1 x Adjust down button 1 x ESC (Auto) button 1 x OK (Menu) button
--------	---

Power

Power Rating	12V DC input 9~36V DC input (Optional)
--------------	---

DIMENSIONS UNIT:MM

